Engraving Parameter for Common Material

Engraving Parameter for Common Material							
Material	Line Interval	Speed	Max-Power	Image Mode	Whether to black out	Number of passes	Case illustration
Basswood	0.1	3000	60%	Jarvis	NO	1	
Pine	0.1	3000	50%	Jarvis	NO	1	
Paulownia Wood	0.1	3000	25%	Threshold	NO	1	
Mahogany	0.1	3000	50%	Threshold	NO	1	
Yellow peach wood	0.1	3000	50%	Threshold	NO	1	
Bamboo	0.1	3000	50%	Jarvis	NO	1	
Leather	0.1	3000	18%	Threshold	NO	1	KIHİSHPO
Denim	0.1	3000	18%	Threshold	NO	1	Bithony
Ceramics	0.1	100	80%	Threshold	YES	1	PLANETA ESCOLA
Ceramic Tile	0.1	100	80%	Threshold	YES	1	

Material	Line Interval	Speed	Max-Power	lmage Mode	Whether to black out	Number of passes	Case illustration
Alumina	0.1	100	80%	Threshold	NO	1	Binkols
Glass	0.1	400	80%	Threshold	YES	1	
Acrylic	0.1	3000	50%	Threshold	NO	1	
Two color plate	0.1	3000	30%	Threshold	NO	1	
Plastic	0.1	1000	20%	Threshold	NO	1	
Resin	0.1	1000	40%	Threshold	NO	1	
Artificial beef bone	0.1	700	70%	Threshold	NO	1	
High density foam board	0.1	3000	30%	Threshold	NO	1	State of the state
Rubber	0.1	1000	70%	Threshold	NO	1	
Kraft Paper	0.1	3000	28%	Jarvis	NO	1	

Material	Line Interval	Speed	Max-Power	lmage Mode	Whether to black out	Number of passes	Case illustration
Office Paper	0.1	1000	15%	Threshold	NO	1	He had been controlled to the head of the
Oil Painting Paper	0.1	1000	10%	Threshold	NO	1	
Carton	0.1	3000	30%	Threshold	NO	1	ATUMSTACK
Density Plate	0.1	3000	25%	Threshold	NO	1	
Mirrors	0.1	3000	35%	Threshold	YES	1	
Galvanized Iron	0.1	100	80%	Threshold	NO	1	
Cobblestone	0.1	1000	80%	Threshold	NO	1	Control of the second
Man Made Rock	0.1	100	80%	Threshold	NO	1	Allani
Rock	0.1	1000	70%	Threshold	NO	1	
PCB Board	0.1	600	80%	Threshold	NO	1	
Brushed Stainless Steel	0.1	100	80%	Threshold	NO	1	

Material	Line Interval	Speed	Max-Power	Image Mode	Whether to black out	Number of passes	Case illustration
Mirror Stainless Steel	0.1	100	80%	Threshold	YES	1	

		C	utting Para		ommon Material
Material	Thickness	Speed	S-Max	Number of passes	Case illustration
Paulownia Wood	6mm	150	80%	10	
	5mm	150	80%	1	150
Basswood	3mm	150	80%	1	
Hardwood	5.5mm	150	80%	3	150 3/h
	5mm	60	80%	1	60
Cork Wood	8mm	900	80%	6	
Bamboo	2mm	250	80%	1	
Acrylic	8mm	50	80%	10	
	3mm	50	80%	1	50
Kraft Paper	0.2mm	3600	80%	1	3600